


BLADE 120CM 36W 3CCT BATTEN CEILING LIGHT



LIGHT SOURCE

Voltage Input

240V

Total Wattage (max)

36

Globe / Light Source qty

1

Globe / Light Source included

Yes

Color Kelvin

3 CCT (3000k - 4000k - 5000k)

Color Temperature

Warm White; Natural White; Cool White

CRI (Color Rendering Index)

>80

Dimmable

No

Globe Type

LED integrated SMD

Lumens

3600

Surge Protection (Yes/No)

Yes

SPECIFICATIONS

Lead and Plug

No

IP rating

IP20

Electrical Protection

CLASS I - HIGH VOLTAGE, EARTH REQUIRED

Beam Angle (degree)

180

Mounting

Surface

COLOUR AND MATERIAL

Fixture Material

Aluminium, Polycarbonate

Fixture Finish

Satin

Diffuser Material

Polycarbonate

PRODUCT DIMENSIONS

Fixture Weight (Kg)

0.65

Fixture Projection (cm)

2.7

Fixture Length (cm)

120

Fixture Width (cm)

7.5

WARRANTY

Replacement Warranty

*3 Years

OTHER

Installation Required

Yes (by Licensed Electrician only)

CARE

Care Instructions

Do not use strong liquid cleaners. Wipe clean with a dry cloth. Aluminium, Brass and Stainless Steel will naturally oxidised and change overtime. Exterior products require regular four (4) monthly cleaning and maintenance to ensure they do not accumulate dirt or other environmental deposits. Wipe the product with a mild detergent and warm water to remove surface deposits. Rinse with fresh water and wipe dry with a soft cloth. An extra temporary protection barrier of water displacement oil can help to maintain the surface, such as WD40, sprayed onto a soft cloth and rubbed onto the surface.

VARIANTS

[BLADE 36-WH3C] BLADE
120CM 36W 3CCT BATTEN
CEILING LIGHT



9329501075371

Find BLADE 120CM 36W 3CCT BATTEN CEILING LIGHT on
www.telbix.com

